



MixRite PVDF Units

Flow rate .5 to 11 GPM

Aflas and Viton O-Rings throughout unit

Enhanced Viton extreme chemical seals

Hastelloy and plastic engine springs for improved chemical compatibility

PVDF body and engine

Internal bypass

Applications:

Sanitizers

Car Wash Chemicals

Chlorinated Chemicals

Harsh Acids

PAA

Iodine

Aggressive Cleaning Agents

Models:

569PVDFONOFF - Injection .1 to .9%

571PVDFIN - Injection .2 to 2%

573PVDFIN - Injection .4 to 4%

World Headquarters: DEMA Engineering Company
10020 Big Bend Blvd. • St. Louis, MO 63122 U.S.A. Tel: 1-800-325-3362 • Fax: 314-965-8319
Web site: www.demaeng.com • E-mail: sales@demaeng.com



We Dispense
SOLUTIONS

SYDNEY, AUSTRALIA • ZEEWOLDE, THE NETHERLANDS • SHANGHAI, CHINA • SÃO PAULO, BRAZIL

MixRite Accessories



50.41.1
Female/Female 3/4" Strainer
3/4" NPT strainer with 80 micron filter cleans up any installation and improves water quality and length of service for MixRite.



57. UFR - Low Flow Booster
Works with any 500 Series MixRite to take low flows (less than .9 GPM) and allows unit to work in conditions without electricity.



57.20.8 - 3/4" Check Valve
Check Valve helps limit backflow situations if unit is being used to pump the mixture a distance.



3803020001
and 93.15.1
3/4" Pressure Regulator & Gauge
Fits inline with any MixRite to limit pressure spikes.



294 DC.DS & 93-18
Compressed Air Foamer and Wand

Compressed Air Foamer and wand can be used with any MixRite air and outlet hose to produce dry "shaving cream" foam.



36073008002
3/4" Anti-Siphon Kit
Fits all 3/4" MixRites inline to relieve pressure so chemical will not siphon out of drum or tank.



40.14QDSS/292QD
Spray Gun and Foam Wand Set
Spray gun and foam wand set can be used with any MixRite and an outlet hose to create wet foam. See video using QR code below.

DEMA

Scan this QR code with your Smartphone and view the MixRite video

